BIOMASA®
PARTNER GROUP

Certified
PREMIUM SELECTION
WOOD PELLET

∅ 6 mm

- guaranteed product quality
- low ash
- high calorific value

EN plus A1 ISO 17225-2 PL 303

EN plus A1 ISO 17225-2 PL 027

www.biomasapartner.pl

Recommended by boiler manufacturers

In harmony with nature

BIOMASA®
PARTNER GROUP

TECHNICAL PARAMETERS

Total moisture content	**< 8%**
Ash content	**< 0.55%**
Calorific value	**> 17.5 MJ/kg**
Bulk density	**600 < BD < 750 kg/m^3**
Fine fraction content (dust in bag)	**< 0.5%**
Mechanical strength	**> 98.0%**
Diameter	**6 mm**
Length	**3.15 < L < 40 mm**

PACKAGING

Unit packaging	**15 kg bags, 1000 kg big bags**
Bulk packaging	**90 x 110 cm pallet/100 x 120 cm**
Bulk	

STORAGE

It is advisable to store the pellets in dry rooms that are not exposed to extreme weather conditions. The bags should be insulated from the ground by being stored on pallets.

PRODUCT CHARACTERISTICS

Production is carried out using pine sawdust without bark or impurities.

The high calorific value and low ash content enable more heat to be obtained from one tonne of pellets.

Held certification guarantees high quality and repeatability of the product batch.

Boiler manufacturers recommend Premium Selection Pellets as the best fuel, as they allow the user to comply with the terms of the boiler warranty.

MANUFACTURER

Biomasa Partner Group SA
tel. +48 534 238 477
e-mail: pellet@biomasapartner.pl

Distribution:

We guarantee safe transport of your pellets!

/BiomasaPartnerGroup

/BiomasaPartnerGroup